

Trawlwire 6 x 7 + FC

6 x (1 - 6) + FC

- ▶ Højre krydsslået - Formlagt
- ▶ Galvaniseret
- ▶ Materialebrudstyrke: 1570 N/mm²

Trawl Warps 6 x 7 + FC

6 x (1 - 6) + FC

- ▶ Right hand ordinary lay - Preformed
- ▶ Galvanized
- ▶ Tensile strength: 1570 N/mm²


1

Varenr. Code no.	Nom. dimension		Konstruktion Construction	Stålareal Steel area mm ²	Ca. vægt Approx. weight kg/m	Min. eff. brudstyrke Min. breaking load	
	mm	Inch*				kN	kp
A07-0070-001M	7,0	9/32	6 x 7 + FC	21,1	0,19	29,9	3.050
A07-0080-001M	8,0	5/16	6 x 7 + FC	26,7	0,23	37,8	3.850
A07-0090-001M	9,0	11/32	6 x 7 + FC	33,0	0,29	47,1	4.800
A07-0100-001M	10,0	13/32	6 x 7 + FC	39,9	0,35	56,9	5.800
A07-0110-001M	11,0	7/16	6 x 7 + FC	47,5	0,42	67,7	6.900
A07-0120-001M	12,0	15/32	6 x 7 + FC	55,7	0,49	79,5	8.100
A07-0130-001M	13,0	1/2	6 x 7 + FC	64,7	0,57	91,2	9.300
A07-0140-001M	14,0	9/16	6 x 7 + FC	74,2	0,66	105,0	10.700
A07-0160-001M	16,0	5/8	6 x 7 + FC	97,0	0,86	137,3	14.000
A07-0180-001M	18,0	23/32	6 x 7 + FC	120,9	1,07	171,7	17.500
A07-0200-001M	20,0	13/16	6 x 7 + FC	147,5	1,30	208,9	21.300
A07-0220-001M	22,0	7/8	6 x 7 + FC	176,7	1,56	251,1	25.600
A07-0240-001M	24,0	15/16	6 x 7 + FC	211,1	1,88	299,2	30.500

* De angivne dimensioner er vejledende.
Ikke angivne dimensioner på forespørgsel.

* Dimensions stated for information only.
Other dimensions on request.

1



Ranco Trawlwire 6x7 + FC

6 x (1 - 6) + FC

- ▶ Højre krydsslået - Formlagt.
- ▶ Min. materialebrudstyrke: Galvaniseret 1570 N/mm².

Varenr. Code no.	Nom. dimension		Konstruktion Construction	Stålareal Steel area mm ²	Ca. vægt Approx. weight kg/m	Min. eff. brudstyrke Min. breaking load	
	mm	Inch*				kN	kp
A07-0070-008S	7,0	9/32	6 x 7 + FC	21,1	0,19	29,9	3.050
A07-0080-008S	8,0	5/16	6 x 7 + FC	26,7	0,23	37,8	3.850
A07-0090-008S	9,0	11/32	6 x 7 + FC	33,0	0,29	47,1	4.800
A07-0100-008S	10,0	13/32	6 x 7 + FC	39,9	0,35	56,9	5.800
A07-0110-008S	11,0	7/16	6 x 7 + FC	47,5	0,42	67,7	6.900
A07-0120-008S	12,0	15/32	6 x 7 + FC	55,7	0,49	79,5	8.100
A07-0130-008S	13,0	1/2	6 x 7 + FC	64,7	0,57	91,2	9.300
A07-0140-008S	14,0	9/16	6 x 7 + FC	74,2	0,66	105,9	10.800
A07-0150-008S	15,0	19/32	6 x 7 + FC	84,4	0,74	119,7	12.200
A07-0160-008S	16,0	5/8	6 x 7 + FC	97,0	0,86	137,3	14.000
A07-0180-008S	18,0	23/32	6 x 7 + FC	120,9	1,07	171,7	17.500
A07-0200-008S	20,0	13/16	6 x 7 + FC	159,7	1,41	225,6	23.000
A07-0220-008S	22,0	7/8	6 x 7 + FC	190,0	1,68	269,8	27.500


* De angivne dimensioner er vejledende.
Ikke angivne dimensioner på forespørgsel.

Ranco Trawl Warps 6x7 + FC

6 x (1 - 6) + FC

- ▶ Right hand regular lay - Preformed.
- ▶ Galvanized. Tensile strength: 1570 N/mm².

* Dimensions stated for information only.
Other dimensions on request.



Trawlwire 6x7 + WSC

6 x (1 - 6) + WSC

- ▶ Højre krydsslået - Formlagt.
- ▶ Galvaniseret.
- ▶ Min. materialebrudstyrke: Galvaniseret 1570 N/mm².

Varenr. Code no.	Nom. dimension		Konstruktion Construction	Stålareal Steel area mm ²	Ca. vægt Approx. weight kg/m	Min. eff. brudstyrke Min. breaking load	
	mm	Inch*				kN	kp
A07-0100-201M	10,0	13/32	7 x 7	48,0	0,41	65,7	6.700
A07-0120-201M	12,0	15/32	7 x 7	66,9	0,56	91,7	9.350
A07-0140-201M	14,0	9/16	7 x 7	89,6	0,76	122,6	12.500
A07-0160-201M	16,0	5/8	7 x 7	117,5	0,99	160,9	16.400
A07-0180-201M	18,0	23/32	7 x 7	148,3	1,25	203,1	20.700
A07-0200-201M	20,0	13/16	7 x 7	181,7	1,53	248,2	25.300
A07-0220-201M	22,0	7/8	7 x 7	232,7	1,96	317,8	32.400

* De angivne dimensioner er vejledende.
Ikke angivne dimensioner på forespørgsel.

Trawl Warps 6x7 + WSC

6 x (1 - 6) + WSC

- ▶ Right hand regular lay - Preformed.
- ▶ Galvanized.
- ▶ Tensile strength: 1570 N/mm².

* Dimensions stated for information only.
Other dimensions on request.